



Product Overview

MT9V022: VGA 1/3" GS CMOS Image Sensor

For complete documentation, see the [data sheet](#)

Product Description

The MT9V022 6µm global shutter HDR pixel technology uniquely allows automotive cameras to “freeze” fast moving objects, and capture all scene detail under extreme lighting conditions. The MT9V022 enhanced NIR pixel process provides excellent image quality in very low-light night conditions.

Features

- High Dynamic Range

Part Electrical Specifications

Product	Compliance	Status	Type	Megapixels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
MT9V022IA7ATC-DP	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		RGB	IBGA-52
MT9V022IA7ATC-DR	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		RGB	IBGA-52
MT9V022IA7ATC-DR1	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		RGB and Mono	IBGA-52
MT9V022IA7ATM-DP	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		Mono	IBGA-52
MT9V022IA7ATM-DR	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		Mono	IBGA-52
MT9V022IA7ATM-DR1	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		RGB and Mono	IBGA-52
MT9V022IA7ATM-FD-DR	AEC Qualified PPAP Capable Pb-free Halide free	Active									IBGA-52
MT9V022IA7ATM-FD-DR-E	Pb-free Halide free	Active									IBGA-52
MT9V022IA7ATM-TP	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		Mono	IBGA-52
MT9V022IA7ATM-TR	AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0		Mono	IBGA-52

For more information please contact your local sales support at www.onsemi.com

Created on: 8/5/2016