

Ver.1.1

Diagonal 14.0 mm (Type 1/1.1) CMOS solid-state Image Sensor with Square Pixel for Monochrome Cameras

## Description

The IMX545-AAMJ is a diagonal 14.0 mm (Type 1/1.1) CMOS active pixel type solid-state image sensor with a square pixel array and 12.41 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, 2.9 V, digital 1.1 V, and interface 1.8 V quadruple power supply. High sensitivity and low dark current characteristics are achieved.

(Applications: FA cameras, ITS cameras)

## Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency 37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 4096 (H) × 3000 (V) approx. 12.28 M pixels
- ◆ Readout mode
  - All-pixel scan mode
  - Vertical / Horizontal 1/2 Subsampling mode
  - 2 × 2 FD binning mode
  - ROI mode
  - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
  - Maximum frame rate in
  - All-pixel scan mode: 8 bit 68.3 frame/s, 10 bit 54.9 frame/s, 12 bit 46.3 frame/s
- ◆ Pulse Output Function
  - The monitor output for Exposure period
  - Programmable pulse output
- ◆ 8-bit / 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
  - 0 dB to 24 dB: Analog Gain (0.1 dB step)
  - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
  - SLVS (2 ch / 4 ch / 8 ch switching) output (594 / 297 / 891 / 445.5 Mbps per ch)
  - SLVS - EC (1 Lane / 2 Lane) output (4.752 / 2.376 / 1.188 Gbps per Lane)
- ◆ Recommended lens F number: 2.8 or more (Close side)

## Pregius S

\* Pregius S is a registered trademark or trademark of Sony Group Corporation or its affiliates. Pregius S is a global shutter sensor technology for active pixel-type CMOS image sensors. By stacking the signal processing on the back illuminated type CMOS Image Sensor it realizes small chip size and high sensitivity, whilst using the high picture quality global shutter pixel technology of Pregius.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

**Device Structure**

◆ CMOS image sensor			
◆ Image size	Diagonal 14.0 mm (Type 1/1.1)	Approx. 12.41 M pixels	All-pixel
◆ Total number of pixels	4128 (H) × 3072 (V)	Approx. 12.68 M pixels	
◆ Number of effective pixels	4128 (H) × 3008 (V)	Approx. 12.41 M pixels	
◆ Number of active pixels	4128 (H) × 3008 (V)	Approx. 12.41 M pixels	
◆ Number of recommended recording pixels	4096 (H) × 3000 (V)	Approx. 12.28 M pixels	All-pixel
◆ Unit cell size	2.74 μm (H) × 2.74 μm (V)		
◆ Optical black	Horizontal (H) direction: Front 0 pixel, rear 0 pixel		
	Vertical (V) direction: Front 64 pixels, rear 0 pixel		
◆ Package	230 pin LGA	20.0 mm (H) × 16.8 mm (V)	

**Image Sensor Characteristics**

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	14510 Digit/lx/s	
Saturation signal	Min.	4094 Digit	

**Basic Drive Mode**

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel	4096 (H) × 3000 (V) approx. 12.28 M pixels	61	SLVS 8 ch	8
		68	SLVS – EC 2 Lane	
		49	SLVS 8 ch	10
		54	SLVS – EC 2 Lane	
		41	SLVS 8 ch	12
		46	SLVS – EC 2 Lane	
Vertical / Horizontal 1/2 subsampling	2048 (H) × 1500 (V) approx. 3.07 M pixels	208	SLVS 8 ch	8
		240	SLVS – EC 2 Lane	
		171	SLVS 8 ch	10
		200	SLVS – EC 2 Lane	
		147	SLVS 8 ch	12
		170	SLVS – EC 2 Lane	
2 × 2 FD binning mode	2048 (H) × 1500 (V) approx. 3.07 M pixels	208	SLVS 8 ch	8
		240	SLVS – EC 2 Lane	
		171	SLVS 8 ch	10
		200	SLVS – EC 2 Lane	
		147	SLVS 8 ch	12
		170	SLVS – EC 2 Lane	

