

Ver.1.0

Diagonal 56.73 mm (Type 3.6) CMOS solid-state Image Sensor with Square Pixel for Color Cameras

---

## Description


The IMX661-AAQR is a diagonal 56.73 mm (Type 3.6) CMOS active pixel type solid-state image sensor with a square pixel array and 128 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, digital 1.2 V, and interface 1.8 V quadruple power supply. (Applications: FA cameras)

---

## Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency 37.125 MHz / 74.25 MHz
- ◆ Number of recommended recording pixels: 13400 (H) × 9528 (V) approx. 127 M pixels
- ◆ Readout mode
  - Various subsampling and readout mode (\*)
  - \* Please refer to the datasheet for binning/subsampling details of readout modes.
- ◆ Readout rate
  - Maximum frame rate in
  - All-pixel scan mode: 10 bit 21.8 frame/s, 12 bit 19.6 frame/s, 14 bit 12.9 frame/s
- ◆ Pulse Output Function
  - The monitor output for Exposure period
- ◆ 11-bit / 12-bit / 14-bit A/D converter
- ◆ CDS / PGA function
  - Analog Gain: 0 dB to 36 dB (0.1 dB step)
- ◆ I/O interface
  - SLVS (4 Lane × 4 IF) output (891 Mbps per ch)
  - SLVS – EC (1 Lane × 4 IF / 2 Lane × 4 IF / 4 Lane × 4 IF) output (4.752 / 2.376 Gbps per Lane)
- ◆ Recommended lens F number: 2.8 or more (Close side)
- ◆ Recommended exit pupil distance: -100 mm

## Pregius

\* Pregius and  are registered trademarks or trademarks of Sony Group Corporation or its affiliates. The Pregius is global shutter pixel technology for active pixel-type CMOS image sensors that use Sony's low-noise CCD structure, and realizes high picture quality.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

## Device Structure

◆ CMOS image sensor		
◆ Image size	Diagonal 56.73 mm (Type 3.6)	
◆ Total number of pixels	13944 (H) × 9764 (V)	Approx. 136.15 M pixels
◆ Number of effective pixels	13472 (H) × 9568 (V)	Approx. 128.90 M pixels
◆ Number of active pixels	13400 (H) × 9528 (V)	Approx. 127.67 M pixels
◆ Number of recommended recording pixels	13400 (H) × 9528 (V)	Approx. 127.67 M pixels
◆ Unit cell size	3.45 μm (H) × 3.45 μm (V)	
◆ Optical black	Horizontal (H) direction: Front 210 pixels, rear 210 pixels Vertical (V) direction: Front 64 pixels, rear 64 pixels	
◆ Package	598 pin LGA	75.0 mm (H) × 63.6 mm (V)

## Image Sensor Characteristics

(T<sub>j</sub> = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	19870 Digit	
Saturation signal	Min.	14890 Digit	

## Basic Drive Mode

Drive mode	Number of active pixels	Max frame rate [frame/s]	Word length [bit]
All-pixel scan mode	13400 (H) × 9528 (V) approx. 127.67 M pixels	21.8	10
Vertical / Horizontal 2/2 weighted binning readout mode	6700 (H) × 4764 (V) approx. 31.91 M pixels	19.5	12
Vertical / Horizontal 2/4 subsampling mode	6700 (H) × 4764 (V) approx. 31.91 M pixels	41.7	10
ROI mode 600 [line]	6700 (H) × 600 (V) approx. 4.02 M pixels	184	10
ROI mode 4 [line]	6700 (H) × 4 (V) approx. 0.026 M pixels	363	10

