

IMX662-AAQR/AAQR1

Diagonal 6.45 mm (Type 1/2.8) CMOS Solid-state Image Sensor with Square Pixel for Color Cameras

Description


The IMX662-AAQR/AAQR1 is a diagonal 6.45 mm (Type 1/2.8) CMOS active pixel type solid-state image sensor with a square pixel array and 2.40 M effective pixels. This chip operates with analog 3.3 V, digital 1.1 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and no smear are achieved through the adoption of R, G and B primary color mosaic filters. This chip features an electronic shutter with variable charge-integration time.

(Applications: Security cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Input frequency: 24 MHz / 27 MHz / 37.125 MHz / 72 MHz / 74.25 MHz
- ◆ Number of recommended recording pixels: 1920 (H) × 1080 (V) approx. 2.07M pixel
- ◆ Readout mode
 - All-pixel scan mode
 - Horizontal / Vertical 2/2-line binning mode
 - Window cropping mode
 - Horizontal / Vertical direction - Normal / Inverted readout mode
- ◆ Readout rate Maximum frame rate in All-pixel scan mode: 12 bit: 60 frame/s, 10 bit: 90 frame/s
- ◆ High dynamic range (HDR) function
 - Digital overlap HDR
 - Clear HDR
- ◆ Synchronizing sensors function
- ◆ Variable-speed shutter function (resolution 1H unit)
- ◆ 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
 - 0 dB to 30 dB: Analog Gain 30 dB (step pitch 0.3 dB)
 - 30.3 dB to 72 dB: Analog Gain 30 dB + Digital Gain 0.3 dB to 42 dB (step pitch 0.3 dB)
- ◆ Supports I/O
 - CSI-2 serial data output (2 Lane / 4 Lane) RAW10 / RAW12 output
- ◆ Anti-reflective coating glass on both sides (IMX662-AAQR1), Non anti-reflective coating glass (IMX662-AAQR)

STARVIS 2

* STARVIS 2 and  are registered trademarks or trademarks of Sony Group Corporation or its affiliates. The STARVIS 2 is back-illuminated pixel technology used in CMOS image sensors for security camera applications. It features a sensitivity of 2000 mV or more per 1 μm² (color product, when imaging with a 706 cd/m² light source, F5.6 in 1 s accumulation equivalent). It also has a wide dynamic range (AD 12 bit) of more than 8 dB compared to STARVIS for the same pixel size in a single exposure, and achieves high picture quality in the visible-light and near infrared light regions.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

- ◆ CMOS image sensor
- ◆ Image size Diagonal 6.45 mm (Type 1/2.8) approx. 2.40 M pixels, All pixels
- ◆ Total number of pixels 2014 (H) × 1196 (V) approx. 2.40 M pixels
- ◆ Number of effective pixels 1965 (H) × 1113 (V) approx. 2.18 M pixels
- ◆ Number of active pixels 1937 (H) × 1097 (V) approx. 2.12 M pixels
- ◆ Number of recommended recording pixels 1920 (H) × 1080 (V) approx. 2.07 M pixels
- ◆ Unit cell size 2.9 μm (H) × 2.9 μm (V)
- ◆ Optical black Horizontal (H) direction: Front 0 pixels, rear 0 pixels
Vertical (V) direction: Front 20 pixels, rear 0 pixels
- ◆ Dummy Horizontal (H) direction: Front 0 pixels, rear 0 pixels
Vertical (V) direction: Front 0 pixels, rear 0 pixels
- ◆ Package 114 pin LGA

Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity (F5.6)	Typ.	18383 Digit/lx/s (IMX662-AAQR) 19556 Digit/lx/s (IMX662-AAQR1)	12 bit converted value
Saturation signal	Min.	3895 Dight	12 bit converted value

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All-pixel	1920 (H) × 1080 (V) approx. 2.07 M pixels	90	CSI-2	10
Horizontal/ Vertical 2/2-line binning	960 (H) × 540 (V) approx. 0.52 M pixels	90	CSI-2	10

Comparison Image under Complex Lighting Environment


IMX662 has a wider dynamic range than conventional type. Also, when shooting a fast-moving target the image taken with Clear HDR does not have chromatic aberration compared to DOL HDR.




Conventional: One shot



IMX662: One shot



Conventional: DOL HDR



IMX662: Clear HDR

