

Ver.1.0

Diagonal 10.04 mm (Type 1/1.6) CMOS Solid-state Image Sensor with Square Pixel for Color Cameras

Description

The IMX676-AACR1 is a diagonal 10.04 mm (Type 1/1.6) CMOS active pixel type solid-state image sensor with a square pixel array and 12.63 M effective pixels. This chip operates with analog 3.3 V, digital 1.1 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and no smear are achieved through the adoption of R, G and B primary color mosaic filters. This chip features an electronic shutter with variable charge-integration time.

(Application: Security cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Input frequency: 24 MHz / 27 MHz / 37.125 MHz / 72 MHz / 74.25 MHz
- ◆ Number of recommended recording pixels: 3536 (H) × 3536 (V) approx. 12.50M pixel
- ◆ Readout mode
 - All-pixel scan mode
 - Horizontal / Vertical 2/2-line binning mode
 - Window cropping mode
 - Horizontal / Vertical direction - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in All-pixel scan mode: 12 bit: 30 frame/s, 10 bit: 60 frame/s
- ◆ Dual Speed Streaming (DSS) function
- ◆ High dynamic range (HDR) function
 - Digital overlap HDR
 - Clear HDR
- ◆ Synchronizing sensors function
- ◆ Variable-speed shutter function (resolution 2H unit)
- ◆ CDS / PGA function
 - 0 dB to 30 dB: Analog Gain 30 dB (step pitch 0.3 dB)
 - 30.3 dB to 72 dB: Analog Gain 30 dB + Digital Gain 0.3 dB to 42 dB (step pitch 0.3 dB)
- ◆ Supports I/O
 - CSI-2 serial data output (2-Lane / 4-Lane / 8-Lane / 4-Lane × 2ch) RAW10 / RAW12 output
- ◆ AR coating on cover glass (Both sides)

STARVIS 2

* STARVIS 2 and its logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates. The STARVIS 2 is back-illuminated pixel technology used in CMOS image sensors for security camera applications. It features a sensitivity of 2000 mV or more per 1 μm^2 (color product, when imaging with a 706 cd/m² light source, F5.6 in 1 s accumulation equivalent). It also has a wide dynamic range (AD 12 bit) of more than 8 dB compared to STARVIS for the same pixel size in a single exposure, and achieves high picture quality in the visible-light and near infrared light regions.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

◆ CMOS image sensor	
◆ Image size	Diagonal 10.04 mm (Type 1/1.6) approx. 12.63 M pixels, All pixels
◆ Total number of pixels	3552 (H) × 3576 (V) approx. 12.70 M pixels
◆ Number of effective pixels	3552 (H) × 3556 (V) approx. 12.63 M pixels
◆ Number of active pixels	3552 (H) × 3552 (V) approx. 12.61 M pixels
◆ Number of recommended recording pixels	3536 (H) × 3536 (V) approx. 12.50 M pixels
◆ Unit cell size	2.0 μm (H) × 2.0 μm (V)
◆ Optical black	Horizontal (H) direction: Front 0 pixels, rear 0 pixels Vertical (V) direction: Front 20 pixels, rear 0 pixels
◆ Package	132 pin LGA

Image Sensor Characteristics

(T_j = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	16309 Digit/lx/s	12 bit converted value
Saturation signal	Min.	3895 Dight	12 bit converted value

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All-pixel	3536 (H) × 3536 (V) approx. 12.50 M pixels	60	CSI-2	10
Horizontal/ Vertical 2/2-line binning	1768 (H) × 1768 (V) approx. 3.12 M pixels	60	CSI-2	10

