

Diagonal 64.84 mm (Type 4.1) CMOS Image Sensor with Square Pixel for Color Cameras

Description

The IMX811-AAQR is a diagonal 64.84 mm (Type 4.1) CMOS active pixel type image sensor with a square pixel array and 247.04 M effective pixels. This sensor incorporates maximum 24 dB PGA circuit and 16-bit A/D converter. 16-bit digital output makes it possible to readout the signals of 247.04 M effective pixels at high-speed of 5.3 frame/s in all-pixel readout mode.

(Application: FA cameras)

Features

- ◆ Type 4.1 CMOS active pixel type dots
- ◆ Input clock frequency 72 MHz
- ◆ All-pixel readout mode
 - Various readout modes (*)
- ◆ Rolling shutter function
- ◆ H driver, V driver and serial communication circuit on chip
- ◆ +24 dB gain settable in CDS/PGA on chip
- ◆ Built-in 12-bit/14-bit/16-bit A/D converter
- ◆ R, G, B primary color mosaic filters on chip
- ◆ Back-illuminated type
- ◆ Sensor Slave Mode only
- ◆ Seal glass: both sides are processed by AR coating
- ◆ SLVS-EC output

* Please refer to the datasheet for binning/subsampling details of readout modes.

Sony reserves the right to change products and specifications without prior notice.

“Sony”, “SONY” logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

- ◆ Back-Illuminated CMOS image sensor
- ◆ Image size Diagonal 64.84 mm (Type 4.1)
- ◆ Total number of pixels 19680 (H) × 13308 (V) approx. 261.90 M pixels
- ◆ Number of effective pixels 19240 (H) × 12840 (V) approx. 247.04 M pixels
- ◆ Number of active pixels 19200 (H) × 12800 (V) approx. 245.76 M pixels
- ◆ Unit cell size 2.81 μm (H) × 2.81 μm (V)
- ◆ Optical black Horizontal (H) direction: Left 188 pixels, right 188 pixels
Vertical (V) direction: Top 56 pixels, bottom 56 pixels
- ◆ Package 786 pin LGA 75.0 mm (H) × 63.6 mm (V)

Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	TBD LSB/lx/s	
Saturation signal	Min.	TBD LSB	

Basic Drive Mode

Drive mode	Number of active pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All-pixel readout mode	19200 (H) × 12800 (V) Approx. 245.76 M pixels	12.4	SLVS-EC Lane 4 × 4	12
		10.5	SLVS-EC Lane 4 × 4	14
		5.3	SLVS-EC Lane 4 × 4	16

Note: All of frame rate are tentative.

