

## [Product Information]

# IMX426LLJ

Ver.1.0

Diagonal 9.2 mm (Type 1 / 1.7) CMOS solid-state Image Sensor with Square Pixel for Monochrome Cameras

---

### Description

The IMX426LLJ is a diagonal 9.2 mm (Type 1 / 1.7) CMOS active pixel type solid-state image sensor with a square pixel array and 0.51 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, digital 1.2 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and low PLS characteristics are achieved.  
(Applications: FA cameras, ITS cameras)

---

### Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency  
37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 812 (H) × 620 (V) approx. 0.50 M pixels
  - Readout mode
  - All-pixel scan mode
  - ROI mode
  - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
  - Maximum frame rate in
  - All-pixel scan mode: 8 bit 1594.7 frame/s, 10 bit: 1449.7 frame/s, 12 bit: 941.4 frame/s
- ◆ Variable-speed shutter function (resolution 1 H units)
- ◆ 8-bit / 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
  - 0 dB to 24 dB: Analog Gain (0.1 dB step)
  - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
  - SLVS (2 ch / 4 ch / 8 ch switching) output (594 / 297 Mbps per 1 ch)
  - SLVS - EC (1 Lane / 2 Lane / 4 Lane / 8 Lane) output (2.376 / 1.188 Gbps per 1 Lane)
- ◆ Recommended lens F number: 2.8 or more (Close side)
- ◆ Recommended exit pupil distance: -100 mm to  $-\infty$

### Pregius

\* Pregius is a trademark of Sony Corporation. The Pregius is global shutter pixel technology for active pixel-type CMOS image sensors that use Sony's low-noise CCD structure, and realizes high picture quality.

Sony reserves the right to change products and specifications without prior notice.

Sony logo is a registered trademark of Sony Corporation.

**Device Structure**

◆ CMOS image sensor				
◆ Image size	Diagonal 9.2 mm (Type 1 / 1.7)	Approx. 0.51 M pixels	All-pixel	
◆ Total number of pixels	816 (H) × 656 (V)	Approx. 0.54 M pixels		
◆ Number of effective pixels	816 (H) × 624 (V)	Approx. 0.51 M pixels		
◆ Number of active pixels	816 (H) × 624 (V)	Approx. 0.51 M pixels		
◆ Number of recommended recording pixels	812 (H) × 620 (V)	Approx. 0.50 M pixels	All-pixel	
◆ Unit cell size	9.0 μm (H) × 9.0 μm (V)			
◆ Optical black	Horizontal (H) direction: Front 0 pixel, rear 0 pixel Vertical (V) direction: Front 32 pixels, rear 0 pixel			
◆ Package	226 pin LGA			

**Image Sensor Characteristics (Preliminary)**

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity (F8)	Typ.	4050 mV	1/30 s accumulation
Saturation signal	Min.	1001 mV	

**Basic Drive Mode**

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel	812 (H) × 620 (V) approx. 0.50 M pixels	752.8	SLVS 8 ch	8
		1594.7	SLVS – EC 8 Lane	
		622.7	SLVS 8 ch	10
		1449.7	SLVS – EC 8 Lane	
		542.7	SLVS 8 ch	12
		941.4	SLVS – EC 8 Lane	